


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b> <b>B01D 27/08</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/14493</b> <b>(43) International Publication Date:</b> 24 April 1997 (24.04.97)
<b>(21) International Application Number:</b> PCT/US96/16772 <b>(22) International Filing Date:</b> 18 October 1996 (18.10.96)  <b>(30) Priority Data:</b> 60/008,127 20 October 1995 (20.10.95) US 60/008,128 20 October 1995 (20.10.95) US 60/005,772 20 October 1995 (20.10.95) US 60/020,754 28 June 1996 (28.06.96) US  <b>(71) Applicant (for all designated States except US):</b> HARVEST TECHNOLOGIES LLC (US/US); 77 Accord Park Drive D-7, Norwell, MA 02061 (US).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> VERKAART, Wesley, H. [US/US]; 77 Accord Park Drive D-7, Norwell, MA 02061 (US). ELLSWORTH, James, R. [US/US]; 77 Accord Park Drive D-7, Norwell, MA 02061 (US).  <b>(74) Agent:</b> CLARK, Conrad, J.; Dickinson, Wright, Moon, Van Dusen & Freeman, Suite 800, 1901 L Street, N.W., Washington, DC 20036 (US).		<b>(81) Designated States:</b> CA, CN, JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> With international search report.
<b>(54) Title:</b> FILTER BAG AND CONNECTOR CARTRIDGE  <b>(57) Abstract</b> <p>A filter bag (200) and connector cartridge are used for collection of physiological fluids. The bag (200) includes an internal filter (206) and two seals (218, 220) on the perimeter. An inner seal (218) bonds the outer sheets (202, 204) of the bag and the filter, while the outer seal (220) bonds only the two outer sheets (202, 204) and acts as a safety seal. The bag includes a verification element that cooperates with a verification connector to ensure that the bag is properly attached to the fluid supply line before a fluid pump is enabled.</p> 		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

5

## **FILTER BAG AND CONNECTOR CARTRIDGE**

### **FIELD OF THE INVENTION**

This invention relates to the art of systems for the collection of fluids. In particular, the invention relates to a bag for receiving fluids and a connector for  
10 connecting the bag to a supply pump.

### **BACKGROUND**

It is known to collect fluids in containers such a flexible bags. For example, it is known to collect blood and other physiological fluids during surgery by pumping  
15 the blood into flexible bags. The fluids are then redelivered to the patient after processing. The fluids generally include debris that must be removed, and filters are used for this. Prior bags that include filters have not been effective, however, and are often expensive. Moreover, because the bags are disposable, the fluid lines are detachable, and it is necessary to provide an effective means for ensuring that the  
20 lines are properly connected before the pumping operation begins.

### **SUMMARY OF THE INVENTION**

In accordance with the invention, a novel bag includes an internal filter, and a connector for attaching the bag to a fluid supply ensures that the bag is properly  
25 connected prior to operation of the pump.

The bag for receiving physiological fluids that have been recovered from a patient includes a filter for removing particles that are larger than a predetermined size. In the preferred embodiment, the filter is a 40 $\mu$  mesh. The bag is made of two layers of flexible plastic with the filter held between the two layers. The inlet to the  
30 bag is placed between the filter and one of the outer layers, and the outlet is placed between the filter and the other of the outer layers. The flexible plastic layers and

the filter are bonded together by heat, radio frequency (RF), or ultrasonic welding at the edges.

The edges are bonded in two locations. First, the filter and the outer layers are bonded completely around the bag inward of the outer edge of the bag, except  
5 for the locations where the inlet and outlet are secured. Then, the two outer layers and inlet and outlet conduits are bonded without the filter between them. By this construction, the bond of all three layers positions the filter to separate the bag into two compartments, and the outer bond acts as a safeguard to ensure that the contents are not spilled even if the inner bond fails.

10 In accordance with another aspect of the invention, a fluid supply line is connected to one or more lines, preferably inlet lines to the bag described above, by a verification connector. The verification connector includes means for verifying that the lines are properly connected and for controlling an interlock that prevents operation of the fluid pumps if the lines are not connected. The verification elements  
15 are easily attached to a base unit for cooperation with verification elements on the base unit to verify that the supply line is properly connected to the outlet lines. In the absence of such verification, operation of the fluid supply pump is inhibited. The verification connectors preferably include known Luer connectors for connecting the supply line to the inlet lines. Other types of connectors may, of course, be used.

20 In the preferred embodiment, the verification elements are optical. A light emitting diode, preferably infrared, and a photo detector, also preferably infrared, are contained in the base unit and are located with respect to the verification elements such that a beam from the light emitting diode will enter a transparent, conducting, portion of the verification elements when properly installed. The inlet line verification  
25 element will refract the light through an angle that will cause it to impinge on a detector in the base unit. Reflecting surfaces may be used to direct the incident and refracted beams to desired locations in the base unit. Signals from the photo detector are supplied to a control circuit that allows operation of a fluid supply pump only when the outlet lines are properly connected.

### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a front view of a filter bag, partially broken away, in accordance with the invention.

Figure 2 is a cross-section taken along line 2-2 of figure 1.

5 Figure 3 is a cross-section taken along line 3-3- of figure 1.

Figure 4 is a cross-section taken along line 4-4 of figure 2.

Figure 5 is a cross-section taken along line 5-5 of figure 4.

Figure 6 is a perspective of a male Luer connector with a mounting key attached.

10 Figure 7 is a perspective of a base element having verification components in accordance with the invention.

Figures 8A and 8B are front views of the base element illustrating attachment of the mounting key to the base element.

Figures 9a and 9B illustrate the operation of the verification elements.

15 Figure 10 is a perspective showing the fluids lines properly connected and attached to the base element.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

20 With reference to figure 1, a filter bag 200 is constructed of respective outer sheets 202 and 204. These sheets are preferably flexible and may be made of known plastic material. An inner sheet 206 is a filter, which is preferably a 40 $\mu$  mesh of plastic material that can be easily bonded to the outer sheets. The bag includes an opening 208 to allow it to be hung from a variety of locations, such as a known I.V. stand.

25 The bag includes an inlet line 210 and an outlet port 212. The inlet line 210 includes a Luer connector 214 for attaching the line to a source of the physiological fluid, such as the supply line shown in figure 6. This connector is preferably designed to connect with other Luer connectors of standard size but also includes means for verifying whether the line is connected to a source of supply. While this  
30 verification element may take various forms, both electrical and mechanical, in the preferred embodiment the verification means is a cylindrical optical element 216.

The cylinder is transparent to light, for example, infrared light from a light emitting diode. When the Luer connector is properly attached to the source of supply, the light passes through the cylinder and is refracted thereby to impinge on a detector. An electronic control circuit senses the presence of light on the detector and, in response, allows activation of a supply pump. This ensures that the line is connected to the source of supply, preventing inadvertently spilling the physiological fluids.

The preferred construction of the filter bag is more clearly shown in figure 2. The three layers of material, the two outer sheets 202, 204 and the filter 206, are bonded together at an inner bond 218. This bond, which may be produced by heating, radio frequency (RF), ultrasound, or other known methods, secures the three layers together to form two chambers 220 and 222 separated by the filter 206. A second, outer bond 220 is formed at the outer edge of the bag. This outer bond is between only the two outer sheets and excludes the filter material. The outer bond 220 provides an additional measure of safety to prevent separation of the two sheets and accidental discharge of the contents of the bag, should the inner bond fail. This is important in situations, such as pressure infusion, where the contents of the bag are subjected to pressures as high as 300mmHg to increase the flow rate.

Figures 4 and 5 show how the sheets 202 and 204 and the filter 206 are secured to the inlet line 210 and the outlet 212. It will be appreciated that the inlet and outlet could as well be attached by a variety of means. For example, these could be provided by a known sidewall connector in each of the sheets 202 and 204.

In operation, physiological fluid, such as blood obtained from a surgical site, is supplied to the inlet line 210 by a pump (not shown). This fluid first flows through the inlet line 210 into the chamber 222. As the fluid passes through the filter into chamber 220, the filter removes unwanted particles. As the bag continues to fill, some of the fluid will remain in chamber 222, while the remainder will pass through the filter to chamber 220. When it is desired to use the fluid in the bag, an appropriate outlet line (not shown), such as an I.V. line is attached to the outlet 212 to permit fluid to flow out of the bag. Preferably, outlet 212 is a known spikeport that has a removable cover 226 and receives a spike in known fashion.

The spikeport includes a flange 228, which may be used to support the bag while it is being filled. When the fluid in the bag is withdrawn, the bag is hung from the opening 208, and the inlet line 210 is closed with a slide clamp, metal crimp, Luer cap, or the like. Thus, the bag is filled in an orientation opposite from the orientation from which it is emptied. This increases efficiency by providing even usage of the filter layer; the in-flowing fluid will pass continuously through one end of the filter as it is filling and the out-flowing fluid will continuously pass through the opposite end of the filter as it is being discharged.

With reference to figure 6, a male Luer connector 302 is attached to a tube 304, as known in the art. A mounting key 306 according to the invention is attached to the Luer connector, as by welding or cement. The key is used to secure the male connector to the base element shown in figures 7 through 10. The base element 308 is attached to, or is a part of, apparatus for pumping fluids into a bag, such as bag 200. The base element includes a face plate 310 for receiving the key 306 and the Luer connector. The face plate includes an opening 312, which is of a shape that will allow the key to be inserted. A narrower notch 314 is located below the opening 312, and a slot 316 is formed between the front of the faceplate and a rear wall thereof. Slot 316 extends vertically from the bottom of the opening 312 to just above the bottom of the faceplate. While the key has been shown to be square, other shapes are possible.

The installation of the key will be explained with reference to figures 8A and 8B. The key 306 with the male Luer connected is first inserted in the opening 312 as shown in figure 8A. Then, the key is slid downward as illustrated in figure 8B, whereby the edges of the key engage the slot 316 to thereby secure the male Luer and key in the faceplate 310. The key is preferably retained in the position shown in figure 8B by gravity; as well the position may be maintained by friction or other mechanisms.

The purpose of this structure is to provide verification of the proper installation of the Luer connectors. Thus, base element 308 includes a source 318 of electromagnetic energy, such as infrared energy from a light emitting diode. The base also includes a window 320 for allowing refracted energy to impinge on a

detector 322. The detector is shown located behind the window, but it could be placed in the element 308 as well. Also, reflectors could be employed to direct the beams as desired to detectors located elsewhere.

Figure 9A illustrates the situation when the female Luer connector 214 is attached to the male Luer connector 302, and the key 306 is secured in the faceplate 310. In this configuration, the light beam 324 is refracted by the optical element 216 on the female Luer. Thus, the light path is as shown in figure 9A where it passes through window 320 and impinges on detector 322. The detector 322 supplies a signal to a control circuit allowing the pumps to operate.

Figure 9B illustrates the situation where the female Luer is not properly connected. In this situation, the required refraction does not occur, and the beam does not pass through the window 322. Accordingly, the detector 322 does not detect the impingement, and the control circuit does not enable operation of the pumps.

Figure 10 shows the male and female Luer connectors attached to each other and installed on the base element. The base element provides an opening at the bottom for receiving the line 304 from the source of fluid, such as a pump. The line 304 and key may be installed from the front of the base element prior to connection of the line 210. Or, the two lines may be attached and then installed in the base element. One advantage of the key, however, is that the connector 214 may be easily attached to the connector 302 with one hand when the key is secure in the base element.

While any number of inlet lines 210 may be used, only one is illustrated in the figures. Thus, supply line 304 may be connected to a Y-connector (not shown), which is in turn connected to the supply pump.

As described above, each of the inlet lines 210 includes a female Luer connector 214 that has been modified to include a verification element. The verification element in the preferred embodiment is the optical element 216 that cooperates with the light source and detector in the base element to verify that the connector 214 is properly in place.



It will be appreciated that the described verification system is fail-safe because it requires a predetermined signal to be received by the photo detectors before connection is verified. If the Luer connectors are not in place, the light from the source in the base unit will not be refracted to the photo detectors, and  
5 verification will be precluded. Modifications within the scope of the claims will be apparent to those of skill in the art.

**We Claim:**

1. A container for a fluid comprising first and second outer sheets forming a cavity and a filter between said sheets dividing said cavity into first and second chambers in communication with each other through said filter, fluid inlet means  
5 communicating with said first chamber for conducting fluid into said cavity, and fluid outlet means communicating with said second chamber for conducting fluid out of said cavity, wherein said sheets and filter are bonded together at a first peripheral bond and only said sheets are bonded together at a second peripheral bond.
2. A container according to claim 1 wherein said first peripheral bond lies radially  
10 inward of said second peripheral bond.
3. A container according to claim 1 wherein said fluid inlet means is secured between a first of said sheets on one side of said inlet means and the other of said sheets and said filter on the other side of said inlet means.
4. A container according to claim 1 wherein said filter comprises a 40 $\mu$  mesh.  
15
5. A container according to claim 1 wherein one of said fluid inlet and fluid outlet means comprises a first connector element and means for verifying proper attachment of said first connector element to a second connector element.
6. A container according to claim 5 wherein said means for verifying comprises  
20 an optical element.
7. A container according to claim 6 wherein said optical element comprises a transparent cylinder.
8. In combination, a first connector element and means for verifying whether said first connector is connected to a second connector element, wherein said  
25 means for verifying comprises an optical element.
9. A combination according to claim 8 wherein said connector is a Luer connector and said optical element comprises a transparent cylinder.
10. A combination according to claim 9 in further combination with a fluid container and wherein said connector is part of an inlet or outlet line for said  
30 container.

11. A combination according to claim 10 wherein said container comprises first and second outer sheets forming a cavity and a filter between said sheets dividing said cavity into first and second chambers in communication with each other through said filter, fluid inlet means communicating with said first chamber for conducting  
5 fluid into said cavity, and fluid outlet means communicating with said second chamber for conducting fluid out of said cavity, wherein said sheets and filter are bonded together at a first peripheral bond and only said sheets are bonded together at a second peripheral bond.
12. Apparatus for connecting two fluid lines, comprising a housing having means  
10 for removably engaging a mounting element on a base unit, a first connector means in fluid communication with a first fluid line and adapted to be removably attached to a second connector means on a second fluid line, and means for verifying that said first connector means is connected to said second connector means.
13. Apparatus according to claim 12 wherein said means for verifying is adapted  
15 to cooperate with verifying means on said base unit when said apparatus is attached to said base unit.
14. Apparatus according to claim 13 wherein said means for verifying comprises means forming at least one optical channel for directing a beam of light toward said second connector means when said second connector means is attached to said  
20 first connector means.
15. Apparatus according to claim 14 wherein said at least one optical channel comprises an inlet channel positioned to align with a light source on said base unit and an outlet channel positioned to align with a light detector when said apparatus is received on said base unit.




FIG. 2




FIG. 5




FIG. 4






FIG. 3





# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US96/16772

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :B01D 27/08

US CL :210/445

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 210/94, 445, 433.1, 455, 461, 494.3

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US 5,269,917 (STANKOWSKI) 14 Dec 1993, col. 3, lines 1-42.	1-3 --- 4-7
X --- Y	US 5,308,483 (SKLAR ET AL.) 03 May 1994, col. 2, lines 59-68, and col. 3, lines 1-3.	1-3 --- 4-7
X	US 5,441,650 (KIRSGALVIS) 15 August 1995, col. 4, lines 1-37.	1-3
X --- Y	US 4,818,190 (PELMULDER ET AL.) 04 April 1989, col. 41, lines 21-56.	8-9, 12-15 ----- 10-11

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z*	document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means		
*P* document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

03 DECEMBER 1996

Date of mailing of the international search report

06 JAN 1997

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

W. L. WALKER

Telephone No. (703) 305-0457